

# EL<sup>®</sup>MARK

The Brand of Electricity

## SKY TL808



# TECHNICAL SPECIFICATION

## INDOOR- SPOTLIGHTS

**ELMARK**<sup>®</sup>

The Brand of Electricity

---

### Technical data:

---

- Rated voltage: 230V/ 50-60Hz
- Power: 15W
- Colour temperature: 2700K; 4000K; 6400K
- Colour: White; Black
- Body: Aluminium
- Beam angle: 90°
- Colour rendering index: Ra≥80
- Switch on/off: >20 000
- Protection against dust and moisture: IP40

---

### Features:

---

- Completely replace traditional lighting fixtures
- Pleasant and uniform light distribution
- Low power consumption
- Repeated switch on/off does not affect the lifespan
- Instant light with maximum luminous flux
- Environmentally friendly - no mercury and lead
- No ultraviolet and infrared rays
- Low heat emission

---

### Area of application:

---

- Commercial sites
- Administrative buildings
- Banks
- Hospitals
- Schools
- Entertainment and leisure spots

MOUSE FOR WORKING STATION

# TECHNICAL SPECIFICATION

## INDOOR- SPOTLIGHTS

# ELMARK®

The Brand of Electricity




### Variants and Dimensions:

#### ■ SKY TL808 TWO LINES

Catalogue number	Watt	Whole fixture lumens	Colour temp.	Size		Colour body	Beam angle	Packing/ Box
				(mm)				
	(W)	(lm)	(K)	Length	Height			(pcs)
93SKY4527	15	1275	2700K	150	210	Black	90°	1/20
93SKY4540	15	1275	4000K	150	210	Black	90°	1/20
93SKY4564	15	1275	6400K	150	210	Black	90°	1/20
93SKY3527	15	1275	2700K	150	210	White	90°	1/20
93SKY3540	15	1275	4000K	150	210	White	90°	1/20
93SKY3564	15	1275	6400K	150	210	White	90°	1/20

#### ■ SKY TL808 FOUR LINES

Catalogue number	Watt	Whole fixture lumens	Colour temp.	Size		Colour body	Beam angle	Packing/ Box
				(mm)				
	(W)	(lm)	(K)	Length	Height			(pcs)
94SKY4527	15	1275	2700K	150	210	White	90°	1/20
94SKY4540	15	1275	4000K	150	210	White	90°	1/20
94SKY4564	15	1275	6400K	150	210	White	90°	1/20
94SKY3527	15	1275	2700K	150	210	White	90°	1/20
94SKY3540	15	1275	4000K	150	210	White	90°	1/20
94SKY3564	15	1275	6400K	150	210	White	90°	1/20



EN 55015 • EN 61000-3-2 • EN 61000-3-3 • EN 61547 • EN 60598-1 • EN 60598-2-2 • EN 61347-1 • EN 61347-2-13 • EN 13032-4

