

LIGHTING FIXTURES

SAMI



Technical data

<i>Rated voltage:</i>	230V/ 50-60Hz
<i>Power:</i>	20W; 40W;
<i>Power supply:</i>	Control gear; DC device- driver, included in the set
<i>Colour temperature:</i>	4000K
<i>LED source:</i>	Epistar
<i>Type of LED:</i>	SMD 2835
<i>Colour:</i>	White
<i>Body:</i>	Aluminium
<i>Reflector:</i>	Plastic matt cover
<i>Colour rendering index:</i>	Ra≥80
<i>Switch on/off:</i>	>20 000
<i>Long life:</i>	30 000h
<i>Protection against dust and moisture:</i>	IP40


Features

- Replacement of conventional fluorescent tubes with highly efficient LED Strip
- Installation: surface ceiling mounting
- Low power consumption
- Repeated switch on/off does not affect the lifespan of the luminaire
- Instant light with maximum luminous flux
- No ultraviolet and infrared rays
- Stable and uniform light distribution

Area of application


- Commercial buildings
- Administrative buildings
- Residential buildings
- Banks
- Hospitals
- Schools

Variants and Dimensions



Watt	Whole fixture lumens	Colour temp.	Colour body	Size (mm)			Catalogue number
				Length	Width	Height	
(W)	(lm)	(K)					
20	1600	4000	White	600	60	40	9SAMI20LED
40	3200	4000	White	1200	60	40	9SAMI40LED

Energy efficiency



Barcodes

3800131192301	9SAMI20LED
3800131192318	9SAMI40LED

Standards

- EN 55015 • EN 61000-3-2 • EN 61000-3-3 • EN 61547 • EN 60598-1 • EN 60598-2-2 • EN 13032-4 •

