

TECHNICAL SPECIFICATION

LED Downlights GL210LED



Technical data

- Power: 2x10W; 2x15W
- Colour temperature: 4000K; 2700K
- Rated voltage: 230V / 50/60Hz
- Lumens /whole fixture/:
 - 2x10W – 1600lm
 - 2x15W – 2400lm
- Light source: LED PLC
- Lampholder: G24d
- Material: sheet steel with aluminium ring
- Body colour: white, satin nickel
- Diffuser : glass with matt dots
- Reflector: aluminum mirror
- Installation: recessed mounting for indoor use
- Protection against dust and moisture: IP20
- Long life: 30 000 hours
- Beam angle: 120°

- Protection against electric shock: I
- Surface requirements: Class F

Areas of application

- Modern Residential Buildings
- Commercial buildings
- Offices
- Hotels
- Recreation facilities

Product benefits

- Lightweight body
- Simple appearance
- Easy installation


Variants and dimensions




Watt	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Size			Catalogue number	Packing (pcs)
				D	H	D1		
2x10W	1600	4000	white	228	110	210	92210LED01	1
2x10W	1600	2700	white	228	110	210	92210LED03	1
2x10W	1600	4000	satin nickel	228	110	210	92210LED02	1
2x10W	1600	2700	satin nickel	228	110	210	92210LED04	1
2x15W	2400	4000	white	228	110	210	92210LED05	1


2x15W	2400	2700	white	228	110	210	92210LED07	1
2x15W	2400	4000	satın nickel	228	110	210	92210LED06	1
2X15W	2400	2700	satın nickel	228	110	210	92210LED08	1

Energy efficiency





This luminaire is compatible with bulbs of the energy classes:





The luminaire is sold with a bulb of the energy class:





92210LED01

874/2012

Barcodes

Barcode	Catalogue number
3800131190079	92210LED01
3800131190086	92210LED02
3800131190093	92210LED03
3800131190109	92210LED04
3800131190116	92210LED05
3800131190123	92210LED06
3800131190130	92210LED07
3800131190147	92210LED08

Standards

EN 55015

EN 61000-3-2; EN 61000-3-3

EN 61547

EN 60598-1; EN 60598-2-2

