

TECHNICAL SPECIFICATION

LED Downlights RDL60COB



Technical data

- Model: 20W; 30W; 40W
- Colour temperature: 4000-4300K / 2700-3000K • Rated voltage: 230V / 50/60Hz
- Lumens /whole fixture/:
 - 20W – 1600lm
 - 30W – 2400lm
 - 40W – 3200lm
- Power Supply: control gear, DC device – driver, mounted in the body
- LED type: COB
- Light source: Epistar Taiwan
- Colour rendering index: Ra≥80
- Switch on/off > 20 000
- Protection against dust and moisture: IP20
- Housing: aluminum
- Colour of the housing: black/white
- Diffuser: glass
- Installation: recessed mounting
- Long life: 30 000 hours
- Beam angle: 60°
- Power factor: $\lambda > 0.9$


Areas of application

- Commercial buildings
- Administrative buildings
- Residential buildings
- Banks
- Hospitals
- Schools
- Entertainment and leisure spots

Product benefits


- Energy-saving fixture in replacement of fluorescent downlights
- Safety, low voltage operation
- Installation in suspended ceilings
- Pleasant and uniform light distribution
- Low power consumption
- Repeated switch on/off does not affect the lifespan
- Instant light with maximum luminous flux
- Environmentally friendly - no mercury and lead
- No ultraviolet and infrared rays
- Resistant to shock and vibration-free body
- Low heat emission
- Compact size

Variants and dimensions




Watt	LED chip lumens (lm)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Size			Catalogue number	Packing (pcs)
					D	H	D1		
20W	2200	1600	4000-4300	black/white	140	77	120	92DL62040	18
20W	2200	1600	2700-3000	black/white	140	77	120	92DL62027	18
30W	3300	2400	4000-4300	black/white	160	110	140	92DL63040	12
30W	3300	2400	2700-3000	black/white	160	110	140	92DL63027	12
40W	4400	3200	4000-4300	black/white	160	110	140	92DL64040	12
40W	4400	3200	2700-3000	black/white	160	110	140	92DL64027	12

Luminous distribution curves



Energy efficiency



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

A++

A+

A

B

C

D


E


X

L

E

D





92DL62040

874/2012

Barcodes

Barcode	Catalogue number
3800131186713	92DL62040
3800131186720	92DL62027
3800131186737	92DL63040
3800131186744	92DL63027
3800131186751	92DL64040
3800131186768	92DL64027

Standards

EN 55015

EN 61000-3-2; EN 61000-3-3

EN 61547

EN 60598-1; EN 60598-2-2

