

TECHNICAL SPECIFICATION

Lamp LED GLOBE G45 FILAMENT



Technical data

- Nominal voltage: 230V/50-60Hz
- Power: 2W; 4W
- Colour temperature: 2700K
- Colour body: mat / clear
- LED type: COB bracket
- Light source: Epistar Taiwan
- Base: E27
- Beam Angle: 360°
- Colour rendering index: Ra≥80
- Average Lifetime: 30 000h
- Switch on/off > 20000


Product benefits

- Lower maintenance cost thanks to longer lifetime
- Reduced operational cost thanks to lower energy consumption.
- Mercury free.
- Maximum resistance to switching loads.
- Correct operation even at low temperature.
- Instant-on light.

Areas of application



- General illumination
- Domestic applications
- Chandeliers
- Outdoor applications only in suitable luminaires

Variants and dimensions



Watt	Colour	LED chip lumens (lm) / LED(pcs)	LED lamp lumens (lm)	Colour temp. (K)	Colour body	Size (mm)		Catalogue number	Packing (pcs)
						Length	Diameter		
2W	warm white	120 / 2	200	2700	mat	72	45	99LED709	100
2W	warm white	120 / 2	200	2700	clear	72	45	99LED719	100
4W	warm white	120 / 4	400	2700	mat	72	45	99LED665	100
4W	warm white	120 / 4	400	2700	clear	72	45	99LED720	100

Energy efficiency



Barcodes

Barcode	Catalogue number
3800131188748	99LED709
3800131188847	99LED719
3800131188854	99LED720
3800131187277	99LED665

Standards

EN 55015

EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-4; EN 61000-4-5; EN 61000-4-8; EN 61000-4-11

EN 61547

EN 62560

